

- **Models**

PCG-GRX700 Series, CTO configurations

- **Processor (Configurable)**

Mobile Intel® Celeron® processor 1.7GHz¹

Mobile Intel® Pentium® 4 processor 1.8, 2.2 or 2.4 GHz¹-M supports Intel® Enhanced SpeedStep™ technology¹

- **Cache Memory**

512 KB integrated on-die level 2

- **Bus Speed**

400 MHz

- **LCD**

16.0" SXGA (1280x1024) TFT display

- **Graphics**

ATI MOBILITY™ RADEON™ 7500

32 MB VRAM (128-bit DDR SDRAM)

Dual display support

- **Memory (Configurable)**

256 MB (256x1), 512 MB (256x2) or 1024 MB (512x2) DDR SDRAM, expandable to 1024 MB

- **Hard Drive (Configurable)**

Removable 30, 40, or 60 GB² hard drive

- **Optical Drive (Configurable)**

Internal removable CD-RW / DVD combo drive (Max speeds: CD-ROM read 24x; CD-RW read 12x; CD-R write 24x; CD-RW write 10x; DVD-ROM read 8x) or,

Internal removable DVD+/-RW/CD-RW drive (Max speeds: DVD-R and -RW write 1x, DVD+R and +RW write 2x, CD-R write 16x, CD-RW write 8x, CD-ROM read 24x, DVD-ROM read 5x)

- **Optional Floppy Drive**

External 1.44 MB, 3.5" USB floppy disk drive (PCGA-UFD5)

- **Memory Stick® Media Slot**

Supports optional Memory Stick® media

- **Hot-Swappable Multi-Bay**

For optical combo drive or optional second battery

- **Modem**

Integrated V.90 modem

- **Ethernet**

10Base-T/100Base-TX Ethernet with RJ-45 interface

- **Pointing Device**

Electro-Static touch pad

- **Estimated Battery Life⁴**

Lithium-ion battery, supports dual battery operation

1.5 - 3.5 hours with one battery ⁴

3.0 - 7.0 hours with optional second battery ⁴

- **PC Card Slots**

2 type I/type II cards, or 1 type III card, CardBus support

- **Audio**

Windows® sound system compatible

Built-in stereo speakers; monoral mini-jack microphone

- **Other Interfaces**

i.LINK® (IEEE 1394) interface ³, AV out (mini-jack), 3 USB, RJ-11 modem jack, RJ-45 Ethernet, Memory Stick® media slot, VGA output, parallel, headphone (stereo), monaural mini-jack microphone, port replicator connection

- **Optional Port Replicator (PCGA-PRGX1)**

PS/2® keyboard and mouse, 2 USB, serial, parallel, VGA output, RJ-45, line-in, line-out, S-video out, TV out, docking

CN

- **Power Requirements**

90 watts maximum $\pm 10\%$ (19.5V/AC100-240V)

Energy Star® compliant

Advanced power management - APM-ACPI compatible

- **Size (H x W x D)**

1.6"-1.8" X 14" X 11.8"

- **Weight**

8.1 lbs. with one battery

8.6 lbs. with battery and optical drive

- **Supplied Accessories**

Lithium-ion battery, power cord, AC adapter, and weight saver