

SONY GRZ600 series

• **Model**

PCG-GRZ610, PCG-GRZ630, PCG-GRZ660
With Microsoft® Windows® XP Home Edition

PCG-GRZ600P1, PCG-GRZ600P3, PCG-GRZ600P6
With Microsoft® Windows® XP Professional

• **Processor**

GRZ610/GRZ600P1
Intel® Pentium® 4 processor 2AGHz¹

GRZ630/GRZ600P3/GRZ660/GRZ600P6
Intel® Pentium® 4 processor 2.40GHz¹

• **Cache Memory**

512 KB integrated on-die level 2

• **Bus Speed**

400 MHz

• **LCD**

15.0" XGA (1024x768) TFT display

• **Graphics**

ATI MOBILITY™ RADEON™ 7500C 32 MB video DDR SDRAM

• **Memory**

GRZ610/GRZ600P1
256 MB DDR SDRAM (256x2), maximum 1024 MB

GRZ630/GRZ600P3/GRZ660/GRZ600P6
512 MB DDR SDRAM (256x2), maximum 1024 MB

• **Hard Drive**

40 GB³ hard drive

• **Optical Drive**

GRZ610/GRZ600P1/GRZ630/GRZ600P3
Internal removable CD-RW/DVD-ROM combo drive
(CD-R-write 24x; CD-RW-write 10x; DVD-read 8x; CD-RW read 12x;

GRZ660/GRZ600P6
Internal removable DVD-RW/CD-RW combo drive¹¹
(CD-R-write 16x; CD-RW-write 8x; DVD-read 8x; CD-RW read 8x; CD-read 24x; DVD-R write 1x; DVD-RW write 1x;
DVD-R/RW read 4x)

• **Optional Floppy Drive**

External 1.44 MB, 3.5" USB floppy disk drive (PCGA-UFD5)

• **Hot-Swappable Multi-Bay**

For optical combo drive or optional second battery

• **Modem**

Integrated V.90 modem

• **Ethernet**

10Base-T/100Base-TX Ethernet with RJ-45 interface

• **Memory Stick. Media Slot**

Supports optional Memory Stick. media

• **Pointing Device / Keyboard**

Electro-Static touch pad
QWERTY, 86 keys with 3mm stroke and 19mm pitch

- **Estimated Battery Life⁴**

Lithium-ion battery, supports dual battery operation
1.5 - 2.5 hours with one battery ⁴
3.0 - 5.0 hours with optional second battery ⁴

- **PC Card Slots**

2 type I/type II cards, or 1 type III card with CardBus support

- **Audio**

Windows® sound system compatible
Built-in stereo speakers; monoral mini-jack microphone

- **Other Interfaces**

RJ-11 modem jack, i.LINK® (IEEE 1394) interface³, 3 USB, AV out (mini-jack), RJ-45 Ethernet, Memory Stick® media slot, VGA output, parallel, headphone (stereo), monaural mini-jack micro-phone, port replicator connection

- **Optional Port Replicator (PCGA-PRGR2)**

DC in, 2 USB, RJ-45 Ethernet, VGA output, PS/2® keyboard and mouse, serial, parallel, S-video out, AV out (mini-jack), line in, docking CN

- **Power Requirements**

115 watts maximum ±10% (19.5V/AC100-240V)
Energy Star® compliant Advanced power management APM-ACPI compatible

- **Size (H x W x D)**

1.7-1.8" X 12.9" X 10.7"

- **Approximate Weight**

6.9 lbs. with one battery
7.5 lbs. with battery and optical drive

- **Supplied Accessories**

Lithium-ion battery, power cord, AC adapter, and weight saver